



Ø 225 mm

Ø 9"

AMP connector Code 180908
AMP terminal Code 42098-2
Suggested mounting torque: 3(+1/-0) Nm with screw M8
Weight 2,35 Kg. approx.

Connettore AMP Cod. 180908
Terminali AMP Cod. 42098-2
Coppia di serraggio consigliata: 3(+1/-0) Nm con vite M8
Peso 2,35 Kg. circa

PRODUCT FEATURES
CARATTERISTICHE PRODOTTO

Waterproof motor, IP 68
Motore chiuso, IP 68



Long life / Lunga durata



suction / aspirante

blowing / soffiante

Static pressure Pressione statica mm H ₂ O	suction / aspirante			blowing / soffiante			Static pressure Pressione statica inH ₂ O
	Airflow Portata m ³ /h	Current input Corrente assorbita A	Airflow Portata CFM	Airflow Portata m ³ /h	Current input Corrente assorbita A	Airflow Portata CFM	
0	1390	4,4	820	1260	4,5	743	0
5	1260	4,6	743	1150	4,7	679	0,2
10	1090	4,8	643	1020	4,9	602	0,4
15	870	4,9	513	840	5,1	496	0,6
20	550	5,0	325	600	5,1	354	0,8
25	430	5,2	254	420	5,3	248	1
30	330	5,4	195	290	5,5	171	1,2
35	210	5,5	124	160	5,6	94	1,4
40	140	5,6	83	0	6,0	0	1,6
45	0	6,0	0				1,8

Test voltage 26 V. D.C. - Tensione di prova 26 V. c.c.