



## DIRECTIONAL LEDs


Beacons | Lightbars | Minibars | Worklamps | Back-Up Alarms | Camera Systems

## 3750 Series

### ECE R65



The 3750 is a high intensity directional LED warning light specifically designed for compact use and R65 approval. The 3750 can also be surface mounted, Collar mounted and L Bracket mounted to the vehicle exterior using the included mounting bezel. Featuring four LEDs that provide exceptional warning. A sealed in-line driver module eliminates the need for a remote power supply. Also features multiple flash patterns and synchronization capability. Additional benefits of LED technology include low current draw and a long maintenance free service life.



In order to meet R65 compliance, must be installed vertically straight up and down

### Models

PART NO.	VDC	AMPS	FLASH PATTERNS	MOUNT
3750X	10-30	1.5	21	Surface, Collar, L Bracket

Replace X in part number with desired LED color: A = amber, B = blue, C = clear, R = red

### Features and Benefits

- Four high-intensity LEDs provide exceptional warning
- Head/tail light or surface mountable using included bezel
- 21 flash patterns
- Multiple heads are synchronizable (simultaneous or alternating operation)
- Colorless when not illuminated
- Operation Temp: -30°C to +50°C
- IP67

### Flash Patterns

#### Sync Patterns

- Single Flash 75FPM
- Single Flash 120FPM \*
- Double Flash 75FPM
- Double Flash 120FPM \*
- Quad Flash 75FPM
- Quad Flash 150FPM
- Triple Alter 75FPM
- Quint Flash 150FPM

#### Non-Sync Patterns

- Steady Burn.
- Module Flash
- Two Double Flash with Triple Flash
- Four Single Flash with Two Quad Flash
- Off

(\* Are R65 patterns)

