



Ø 255 mm

Ø 10"

AMP connector Code 180908
 AMP terminal Code 42098-2
 Suggested mounting torque: 3(+1/-0) Nm with screw M8
 Weight 2,25 Kg. approx.

Connettore AMP Cod. 180908
 Terminali AMP Cod. 42098-2
 Coppia di serraggio consigliata: 3(+1/-0) Nm con vite M8
 Peso 2,25 Kg. circa

PRODUCT FEATURES CARATTERISTICHE PRODOTTO

Waterproof motor, IP 68
 Motore chiuso, IP 68



Long life / Lunga durata



suction / aspirante

blowing / soffiante

| Static pressure Pressione statica mm H ₂ O | suction / aspirante | | | blowing / soffiante | | | Static pressure Pressione statica inH ₂ O |
|---|---|--|---------------------------|---|--|---------------------------|--|
| | Airflow Portata m ³ /h | Current input Corrente assorbita A | Airflow Portata CFM | Airflow Portata m ³ /h | Current input Corrente assorbita A | Airflow Portata CFM | |
| 0 | 1870 | 10,5 | 1103 | 1750 | 9,6 | 1033 | 0 |
| 5 | 1670 | 11,3 | 985 | 1560 | 10,4 | 920 | 0,2 |
| 10 | 1440 | 12,0 | 850 | 1380 | 11,0 | 814 | 0,4 |
| 15 | 1000 | 11,4 | 590 | 1120 | 11,7 | 661 | 0,6 |
| 20 | 720 | 12,4 | 425 | 810 | 11,9 | 478 | 0,8 |
| 25 | 530 | 12,7 | 313 | 540 | 12,4 | 319 | 1 |
| 30 | 390 | 13,2 | 230 | 300 | 12,8 | 177 | 1,2 |
| 35 | 310 | 13,5 | 183 | 210 | 13,2 | 124 | 1,4 |
| 40 | 0 | 15,4 | 0 | 0 | 14,4 | 0 | 1,6 |

Test voltage 13 V. d.c. - Tensione di prova 13 V. c.c.